

CS118v2-WR

18 inch Subcardioid Subwoofer



Overview

The CS118v2-WR is a subcardioid subwoofer module intended for permanent installation in a wide range of outdoor venues. It includes a single, high power 18 inch direct-radiating woofer in a compact, IP55 weather-resistant enclosure. A variety of mounting points facilitate suspension via user-supplied shoulder eye bolts or an optional yoke bracket.

The CS118v2 incorporates Fulcrum's patent-pending *Passive Cardioid Technology™* to overcome one of the major challenges of many loudspeakers: excessive rear LF radiation. Unlike active cardioid loudspeakers, Fulcrum's passive cardioid technology does not require an additional amplifier channel or additional transducer to achieve its impressive low frequency directional control: 10 dB of rear rejection over the subwoofer's operating range.

The subcardioid behavior is produced by a meticulously conceived acoustical circuit which balances the position of the low frequency driver, the enclosure depth and volume, and specially constructed rear-mounted ports which include a calibrated resistive element. By opting for a subcardioid pattern as opposed to a pure, hyper or super cardioid pattern, the rear rejection increases when the modules are deployed in a subwoofer array.

Fulcrum Acoustic's **TQ™** processing is an integral part of the CS118v2 design. Sound, innovative acoustical design combined with state of the art digital processing leads to exceptional clarity and precise transient response, even at very high sound pressure levels. The required digital signal processing can be provided by one of many supported platforms.

Performance Specifications¹

Operating Mode

Single-amplified w/ DSP

Operating Range²

29 Hz to 137 Hz

Nominal Beamwidth

Subcardioid (10 dB rear rejection) within operating range

Transducers

LF: 18.0" woofer, 4.0" voice coil; ceramic magnet

Power Handling @ Nominal Impedance³

98 V / 1200 W @ 8 Ω

Nominal Sensitivity @ Input Voltage⁴ (half / whole space)

103 dB / 97 dB @ 2.83 V

Nominal Maximum Continuous SPL (half / whole space)

140 dB / 134 dB peak
134 dB / 128 dB continuous

Equalized Sensitivity @ Input Voltage⁵ (half / whole space)

100 dB / 94 dB @ 2.83 V

Equalized Maximum SPL⁶ (half / whole space)

136 dB / 130 dB peak
130 dB / 124 dB continuous

Recommended Power Amplifier

1200 W to 1800 W @ 8 Ω

Physical Specifications

Connections

(1) Terminal Strip
Pin 1+/-: LF
Pin 2+/-: No Connection

Mounting / Suspension Points

(16) M10 x 1.5 eye bolt angle points, (2) M12 x 1.75 yoke points

Dimensions / Weight

See page 4

Finish


Black painted enclosure w/ matte black grille

Options


YK-FH15 Ceiling Mount Yoke Bracket, Custom color finish

preliminary product specification


Axial Sensitivity (dB SPL, 2.83 V @ 1 m, half space)^{7,8}



Axial Processed Response (dB, half space)^{7,9}




Impedance (ohms)



preliminary product specification

Connection Diagram

1-way, Single-Amp



Mechanical Specification Drawings

2D and 3D DWG dimensional drawings are available for download at www.fulcrum-acoustic.com/resources


Notes

- ¹ **Performance Specifications** All acoustic specifications rounded to nearest whole number.
External DSP with Fulcrum Acoustic-provided settings is required to achieve the specified performance.
- ² **Operating Range** The frequency range within which the processed response is within 10 dB of the average.
- ³ **Power Handling** Based on the AES power handling of the transducers.
- ⁴ **Nominal Sensitivity** The 1-meter-referenced SPL produced by a 1 watt band limited pink noise signal, with no processing applied.
- ⁵ **Equalized Sensitivity** The 1-meter-referenced SPL produced when an EIA-426-B signal is applied to an equalized loudspeaker system, at a level which produces a total power of 1 watt, in sum, to the loudspeaker subsections.
- ⁶ **Equalized Maximum SPL** The 1-meter-referenced SPL produced when an EIA-426-B signal is applied to an equalized loudspeaker system, at a level which drives at least one subsection to its rated power.
- ⁷ **Resolution** All response graphs are subjected to 1/6 octave cepstral smoothing with a gaussian weighting function.
- ⁸ **Axial Sensitivity** The SPL plotted against frequency for a 1 watt swept sine wave, referenced to 1 m with no signal processing.
- ⁹ **Axial Processed Response** The axial magnitude response with recommended signal processing applied.



fulcrum
ACOUSTIC®

preliminary product specification



Drawing is reduced. Do not scale.



fulcrum
ACOUSTIC®





optional accessory

NOTES:


1. FITS: FH15xx Series, CS118, CS121
2. NET WEIGHT: 17.0 lb / 7.7 kg
3. MATERIAL: 7 GA ASTM A36 STEEL
4. INCLUDES HARDWARE KIT
5. USE FOR OVERHEAD CEILING MOUNT ONLY

REVISIONS


REV	DESCRIPTION	APPR / DATE
1	NEW ISSUE	RAF 4/21/20
2	ADD CS SUBS TO NOTE 1	RAF 5/6/20
3	ADD BRACKET MATERIAL TO NOTES	RAF 8/5/21
4	UPDATED MOUNTING HOLE SPACING	RAF 3/4/22
5	ADD 'CEILING MOUNT' TO DESCRIPTIONS	RAF 4/4/23



INDEX PLATE (2 pcs)



THIRD ANGLE PROJECTION



THIS DRAWING IS THE PROPERTY OF FULCRUM ACOUSTIC, AND SHALL NOT BE COPIED, REPRODUCED, OR USED AS THE BASIS FOR MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN AUTHORIZATION. DO NOT SCALE DRAWING.

UNLESS OTHERWISE SPECIFIED:
ALL DIMENSIONS ARE IN INCHES

TOLERANCE IN INCHES
.XX±.015 .XXX±.005
FRACTIONS ±1/32
ANGLES ±1/2°

(X.XX) = REF DIMS NO TOLERANCE IMPLIED

TSC = THEORETICAL SHARP CORNER

DIMENSIONS ACROSS CENTERLINES
TO BE SYMMETRICAL

STATUS RELEASED

APPROVALS	DATE
DRAWN: RAF	4/21/20
CHECKED: DEW	4/21/20
DES ENG:	
MFG ENG:	



FULCRUM ACOUSTIC, LLC
670 LINWOOD AVE, LINWOOD, MA 01525 USA

TITLE: Mech Spec, YK-FH15
Ceiling Mount Yoke Bracket

A SHEET 1 OF 1 SCALE: 1:12


DWG. NO. 820-300-025 REV 5

Drawing is reduced. Do not scale.



fulcrum
ACOUSTIC®

optional accessory



Drawing is reduced. Do not scale.